

# PHOTO TACHOMETER

Model : DT-2234A



SPECIFICATIONS	
Measurement Range	5 to 99,999 RPM.
Resolution	0.1 RPM < 1,000 RPM 1 RPM 1,000 RPM
Display	5 digits, 10 mm (0.4") LCD.
Accuracy	± (0.05% + 1 digit).
Sampling Time	1 sec. (60 RPM).
Time base	Quartz crystal.
Detecting distance	50 to 150 mm / 2 to 6 inch. <i>* Typical max. 300 mm / 12 inch depending upon ambient light.</i>
Circuit	Exclusive one-chip of microcomputer LSI circuit.
Battery	1.5 V AA (UM-3) battery x 4 PCs.
Operating temperature	0°C to 50°C (32°F to 122°F).
Operating humidity	Less than 80% RH.
Memory	Last value, Max. value, Min. value.
Size	190 x 72 x 37 mm (7.5 x 2.8 x 1.5 inch).
Weight	250g (0.55 LB)/including battery.
Accessories	Carrying case ..... 1 PC. Reflecting tape marks (600 mm)..... 1 PC. Operation manual ..... 1 PC.

OTHER TACHOMETERS & STROSCOBOSCOPES	
DT-2235B	Contact tachometer, 0.5 to 19,999 RPM.
DT-2236	Photo & contact tachometer. 0.5 to 99,999 RPM.
DT-2244	Photo tachometer, 5 to 99,999 RPM.
DT-2245	Contact tachometer, 0.5 to 19,999 RPM.
DT-2238	Photo & contact tachometer. 0.5 to 99,999 RPM.
DT-2239	Digital stroboscope, 100 to 1000 RPM/FPM.
DT-2249	Digital stroboscope, 12 to 12000 RPM/FPM.
DT-2259	Photo tachometer + Digital stroboscope, 2 in 1.