



**2 wires**

# DISSOLVED OXYGEN TRANSMITTER

Model : TR-DOT2W

<b>Features</b>	2 wires, both for signal and power supply.
<b>Measure Range</b>	<i>Range 1 :</i> $O^2$ CAL.  <i>Range 2 :</i> DO : 0 -20 mg/L
<b>Output</b>	4 - 20 mA  <i>Range 1 ( CAL ) :</i> 20.9 % $O^2$ = 12 mA  <i>Range 2 ( DO ) :</i> 0 mg/L = 4 mA 10 mg/L = 12 mA 20 mg/L = 20 mA
<b>External Adjustment</b>	ZERO VR SPAN VR
<b>Power Supply</b>	90 - 30 VDC.
<b>Operation Temperature</b>	0 - 50 °C 32 - 122 °F
<b>Operation Humidity</b>	Less than 80 %RH
<b>Accessory Included</b>	Dissolved Oxygen Probe Probe-filling electrolyte, OXEL-03 Spare diaphragms, OXDP-02
<b>Optional Accessories</b>	Probe-filling electrolyte, OXEL-03 Spare diaphragms, OXDP-02
<b>Mounting</b>	Din rail or Wall, socket is included.
<b>Case</b>	ABS plastic
<b>Others</b>	Separate probe with plug

