



Nova-Strobe dbx

Common Applications:

- Non-contact RPM
- Diagnostic Inspection
- Bent blades/shafts
- Slipping/worn belts
- Printing Press
- Stop-action Inspection
- Textiles



Optional protective rubber cover

Nova-Strobe x - The standard for high intensity multi-function portable stroboscopes. Models are available with digital displays, battery or AC power, and a useful range of features which provide unmatched performance and value. Four models range from the Nova-Strobe **dbx** Deluxe, the most versatile battery powered digital stroboscope with internal phase shifting, down to the Nova-Strobe **bax** Basic, the most cost effective AC powered digital stroboscope.

Both the battery powered Nova-Strobe **dbx** and AC powered Nova-Strobe **dax** provide a range of 30 to 20,000 flashes per minute and an accuracy of ± 0.002 of setting. Flash rates are easily adjusted to fractional RPM by a coarse/fine control knob. Individual TTL compatible input and output jacks are provided for 'daisy chaining' of multiple strobes, triggering from an external source, or providing a trigger signal to external equipment.

Both dbx and dax provide internal phase shifting to keep the target precisely in view. Both provide x2 and $\div 2$ capability for distinguishing actual RPM from harmonic frequencies. In addition, 9 user presettable memory flash rates for repetitive measurements and storage of the last flash rate measured are included.

Features All Nova-Strobes, Deluxe and Basic:

- Internal rechargeable batteries or AC powered models
- Weighs less than 2.0 Lbs. for easy handling
- More than 20% brighter Xenon light than competitors
- Electronic switching provides continuous cool operation
- Tripod mounting bushing in handle
- Low battery indicator (for battery powered models)

In addition, Nova-Strobe **dbx** and **dax** Plus models have:

- N.I.S.T. Traceable Certificate of Calibration included
- Internal phase shifting for easy reference target viewing
- Tachometer mode, speed measurement up to 250,000 RPM
- Power for optional sensors

Select optional sensors for tachometer mode (see page 9)

TTL compatible input/output
1/8" (3.5mm) phone plugs

Nova-Strobe **bbx/bax** Basic Digital LCD Display



Nova-Strobe dbx Kit

Nova-Strobe dbx
Deluxe

Ordering Information

Nova-Strobe **bax** 115 Stroboscope, AC powered
 Nova-Strobe **bax** 230 Stroboscope, AC powered
 Nova-Strobe **dax** 115 Stroboscope, AC powered
 Nova-Strobe **dax** 230 Stroboscope, AC powered
 Nova-Strobe **bbx** 115/230 Stroboscope, battery
 Powered, universal PSC-2U (115/230 VAC)
 recharger (USA, UK, AUS, EURO plug)
 Nova-Strobe **dbx** 115/230 Stroboscope, battery
 powered, universal PSC-2U (115/230 VAC)
 recharger (USA, UK, AUS, EURO plugs)
 Also available in Kit form including: Stroboscope
 Recharger, spare lamp and carrying case.

Specifications	Nova-Strobe dbx, Deluxe Battery Powered	Nova-Strobe dax, Deluxe AC Powered	Nova-Strobe bbx, Basic Battery Powered	Nova-Strobe bax, Basic AC Powered
Range Flashes/Minute	30-20,000 FPM (Flashes Per Minute)		30-10,000 FPM (Flashes Per Minute)	
Display	6 Digit Numeric and 5 digit Alphanumeric LCD			
Accuracy/Resolution	0.002% of setting or +/- 1 lsd /0.01 FPM			
Flash Energy/Duration	230 mJoule up to 3450 FPM / 8-20 μ sec			
Average Power-Watts	>13W above 3450 FPM			
Flash Tube & Life	High Power Xenon - 100 million flashes typical			
External Triggers - in/out 1/8" (3.5mm) Phone Jacks	TTL (24Vdc Max) Input. Provides 3.3 Vdc TTL output		N/A	
Tachometer Mode	5-250,000 RPM - Use with Optional Remote Sensor		N/A	
Programmable Memory	Yes	Yes	N/A	
Internal Phase Shift	Yes	Yes	N/A	
Operating Time	2 hours typical @ 1800 FPM	Continuous	2 hours typical @ 1800 FPM	Continuous
Power Supply	Internal NiMH rechargeable batteries	115 Vac, 50-400 Hz or 230 Vac, 50-400 Hz	Internal NiMH rechargeable batteries	115 Vac, 50-400 Hz or 230 Vac, 50-400 Hz
Weight	1.9 Lbs. (.86 kg)	1.5 Lbs. (0.68 kg)	1.9 Lbs. (.86 kg)	1.5 Lbs. (0.68 kg)
Size (L x W x H)	Body: 9" x 3.66" x 3.56" (229 x 93 x 90 mm); Reflector Housing: 4.8" (122 mm) diameter; Handle: 4.25" (108 mm) long			

Phaser-Strobe pbx

RoHS NIST CE

The **Phaser-Strobe pbx** incorporates the unique design features of the Nova-Strobe dbx with an increased operating range of 30 to 50,000 flashes per minute, as well as external phase shifting. The unique digital adjustment knob can select the decade for adjustments, so coarse and fine adjustments of flash rates are made quickly and with significantly better resolution than competitive units. The memory feature of the **Phaser-Strobe pbx** allows nine flash rates to be stored - displayed in flashes per minute or flashes per second. **Phaser-Strobe pbx** operates with internal rechargeable batteries or continuously from AC line power with the power supply/recharger.

Features:

- N.I.S.T. Traceable Certificate of Calibration included
- Phase Shift adjustable as phase angle or time with resolution to 0.01° and 0.01 msec
- Virtual RPM mode provides slow motion viewing for high speed events
- Backlit alphanumeric LCD shows flash rate, degrees, time
- Store and recall nine memory settings
- TTL compatible input/output jacks, power for optional sensors
- Tachometer mode from Remote Sensors (see page 9)

Specifications	Phaser-Strobe pbx
Flash Range	30-50,000 FPM (Flashes/Minute) 0.5-830 FPS (Flashes/Sec) (Hz)
Accuracy	±0.002% of Setting +/- least significant digit
Digital Adjustment Knob	36 detents per revolution and blinking decade selection
Flash Rate Resolution (Internal Triggering)	0.01 to 1.0 FPM (Menu Selectable)
Operating Time	2 hours typical @ 1800 FPM or continuous AC power
Phase Delay - Degrees	0.1 to 359.9 degrees
Time Delay - Seconds	0.01 to 1000 msec.
Virtual RPM (Slow Motion)	0-200 VRPM
Flash Energy (Typical)	230mJoule up to 3450 FPM
Flash Duration (Typical)	8-20 usec
Average Power - Watts	11W @ 3000 FPM; >13W @ 3450 FPM
Tachometer Mode	5-250,000 RPM from external trigger
External Input	Input Pulse - 0.5 usec min, TTL to 24V max (1/8" phone plug)
Trigger Output/Remote Sync	3.3V TTL Compatible 40 usec pulse-Positive/Negative
Power	Internal rechargeable batteries with AC power supply/recharger
Weight	1.9 Lbs. (0.85 kg) including batteries



Phaser-Strobe pbx



Common Applications:

- Calibration of Tachometers
- Diagnostic Inspection
- Engine R&D
- Textiles
- Centrifuges
- Shaker Tables



Compatible with Remote Sensors (see page 9).

Ordering Information
 Phaser-Strobe pbx 115/230 - Stroboscope with PSC-pbxU (115/230 Vac) Power Supply/Recharger
 Phaser-Strobe pbx Kit 115/230 - Same as above with Spare Lamp and Latching Carrying Case

PORTABLE STROBOSCOPES (for use with Vibration Data Collectors)

Vibration-Strobe vbx

RoHS NIST CE

The **vbx vibration strobe** is uniquely designed to provide precise, instantaneous synchronization to a number of data collectors and FFT Analyzers triggered by an accelerometer. Built for portable applications, the **vbx** is the perfect lightweight phase analysis tool. **vbx** allows for the measurement of phase without stopping the machinery to install reflective tape. Phase analysis is quick and accurate using the Filter Bandwidth Selector and the Relative Phase Adjustment. Unique "Tracking Filter" maintains phase lock to input pulse. **vbx** can power and be triggered by accelerometers with or without data collectors.

Kit includes: Strobe, accelerometer interface cable, universal p.s./recharger, spare lamp in carry case.

Specifications	Vibration-Strobe vbx
Flash Range	30-50,000 FPM (Flashes/Minute) 0.5-830 FPS (Flashes/Sec) (Hz)
Accuracy	±0.002% of Setting +/- least significant digit
Digital Adjustment Knob	36 detents per revolution and blinking decade selection
Flash Rate Resolution (Internal Triggering)	0.01 to 1.0 FPM (Menu Selectable)
Indicators	Battery Level, On Target, Time, Auto, Alt, Tach, Lock, and EXT icons
Operating Time	2 hours typical @ 1800 FPM or continuous AC power
Phase Delay - Degrees	0.1 to 359.9 degrees
Tracking Filter	Selectable Wide and Narrow Bandwidths. Filter may not lock below 100 fpm
Time Delay - Seconds	0.01 to 1000 msec.
Virtual RPM (Slow Motion)	0-200 VRPM
Flash Energy (Typical)	230mJoule up to 3450 FPM
Flash Duration (Typical)	8-20 usec
Average Power - Watts	11W @ 3000 FPM; >13W @ 3450 FPM
Tachometer Mode	5-250,000 RPM from external trigger
External Input	Input Pulse - 0.5 usec min, TTL to 24V max (1/8" phone plug)
Trigger Output/Remote Sync	3.3V TTL Compatible 40 usec pulse-Positive/Negative
Power	Internal rechargeable batteries with AC power supply/recharger
Weight	1.9 Lbs. (0.85 kg) including batteries



Vibration Strobe vbx



Ordering Information
 Contact Factory for available Models.