



GASTRANSMITTER

GTR 210





Application

The gas transmitter ADOS GTR 210 is suitable for continuous measurement of gases in normal areas and areas where there are risks of explosion.

By employing 6 different types of sensor, noxious, explosive and non-combustible gases and vapours can be measured.

Display of the measured gas concentration and the adjustable alarm thresholds, are shown on a multi-colour graphic display. The keyboard input is by way of a touchpad.


A current signal is generated that is proportional to the measured concentration of gas, which is transmitted to an evaluation unit placed in a safe area, away from any dangers of explosion.

The type test of the explosion-protected gas transmitter, is completed by the KEMA.

KEMA test certificate: No.: KEMA
Type of protection: Ex d e ia mb IIC T4 Gb

Fields of Application

- Chemical industry
- Manufacture of paints and varnishes
- Plastic processing plants
- Sewage works
- Gas-fired boiler systems
- Liquid gas storage houses
- Laboratories
- Oxygen concentration measurement
- Refineries
- Cold-storage houses (Ammonia monitoring)
- Paint spraying booths
- and many more




1 = Circuit voltage
2 = Heating voltage
3 = Load resistor

The TGS sensor

The TGS sensor contains a semiconductor sensor, which is constructed on SnO₂-sintered N-substrate.

When combustible or reducing gases are absorbed by the surface of the sensor, the concentration of the test gas is determined by the change in conductivity.




1 = Catalyzer pellistor
2 = Electric connections
3 = Inert pellistor
4 = Diffusion filter


The VQ sensor

The head of the VQ sensor functions on the principle of heat reaction. When combustible or reducing gases or vapours come in contact with the measuring element, they are subjected to catalytic combustion, which causes a rise in temperature; this rise causes a change in the resistance of the measuring element which is used as a measure of the component of gas being tested.


The inert element is for compensating the temperature and conductivity of the test gas.




- 1 = Diffusion filter
- 2 = Test resistor
- 3 = Comparison resistor



- 1 = Anode
- 2 = Electrolyte
- 3 = Cathode
- 4 = Diffusion path
- 5 = Diffusion filter
- 6 = Test gas



- 1 = Infrared-radiating source
- 2 = Test gas
- 3 = Diffusion filter
- 4 = Infrared-detector
- 5 = Measurement chamber



- 1 = UV radiating source
- 2 = Test gas
- 3 = Capacitive charge measurement

The GOW sensor

The GOW sensor functions on the principle of thermal conductivity. Two rhenium-tungsten resistors are used as a measuring element, where the comparison element is subjected to normal ambient air and the measuring element is subjected to the test gas. Any change in the concentration of gas at the measurement element, causes a change in temperature, which is due to the variation of conductivity. The resultant change in resistance is a direct measure of the gas concentration.

The TOX sensor

The TOX sensor is a measurement system with electrochemical cell, where the sampled gas is measured by diffusion. In the case of oxygen measurement the oxygen content is in an electrolyte, thus producing a small flow of current (electro-chemical process). At a constant air pressure, this current is directly proportional to the oxygen concentration in the sampled air.

The IR sensor

The test gas flows through a measurement chamber that incorporates an IR radiating source and a two-channel infrared detector. The intensity of the infrared radiation is reduced as it passes through the gas molecules. The concentration of the gas can then be calculated by the magnitude of the reduction in intensity. Since only absorption of the wavelength specific to the gas under test in relation to the wavelength not absorbed by a test gas is considered, interference due to dust, ageing etc., is almost compensated.

The PID sensor

The sampled gas flows through a measurement chamber, that incorporates a UV radiating source and a pair of electrodes with opposing polarity. The gas molecules to be detected are ionized by the UV radiation. The resulting positively charged molecules and the electrons are attracted to the relevant electrode. The current generated is a measure of the gas concentration. Using the PID measuring head, volatile organic compounds (VOC) can be measured, the ionisation potential of which is less than the energy in the UV radiating source (10,6 eV), e.g. aromatic hydrocarbons like toluol (C₇H₈) and xylene (C₈H₁₀) as well as chlorinated hydrocarbons like trichloroethylene (CHCl₃). The detection of toxic gases like phosphine (PH₃) is also possible.

The output signal of each sensor is connected to the central unit via a multicore cable for further processing. All sensors are plug-in types and thus are easily replaceable.



Technical Data

Type	TGS	VQ	GOW	TOX	IR	PID
Measurement method	Semiconductor	Heat reduction	Thermal conductivity	Electro-chemical reaction	Infrared	Photo-Ionisation
Measurement range	ppm ranges to 100 % LEL	ppm ranges to 100 % LEL	from 0–5 Vol % to 0–100 Vol %	ppm ranges to 0–100 Vol %	0-100 % LEL CH ₄ , C ₃ H ₈ , C ₂ H ₂ 0-100 Vol % CH ₄ 0–1, 2, 3, 4, 5 Vol % CO ₂	0–200 ppm to 0–2.000 ppm
Percentage error of f.s.d.	± 5%	± 5%	± 5%	± 3%	± 3%	± 5%
Temperature range	-25 °C to +55 °C	-25 °C to +55 °C	-25 °C to +55 °C	-25 °C to +55 °C	-25 °C to +55 °C	-25 °C to +55 °C
Temperature effect	5%	2%	2%	2%	2%	2%
Response time (t ₉₀)	approx. 20 s	approx. 20 s	approx. 40 s	< 60 s	< 30 s	approx. 60 s
Pressure effect	1%	1%	1%	1%	1%	1%
Mounting position	optional	optional	optional	optional	optional	optional
Application	Poisonous, combustible and explosive gases in the LEL region	Poisonous, combustible and explosive gases in the LEL region	gases exhibiting substantial differences in thermal conductivity, compared to air	O ₂ , CO, NH ₃ , NO ₂ , SO ₂ , H ₂ S and others	CH ₄ (Vol %; LEL) Propan (LEL), CO ₂ (Vol %)	e.g. C ₂ H ₆ , C ₈ H ₁₀ CHCl ₃ , PH ₃
Versions available	industrial (AI), industrial (VA)- and Ex-version	industrial (AI), industrial (VA)- and Ex-version	industrial (AI), industrial (VA)- and Ex-version	industrial (AI), industrial (VA)- and Ex-version	industrial (AI), industrial (VA)- and Ex-version	industrial (AI), industrial (VA)- and Ex-version
Expected lifetime of the sensor	unlimited, when used for gases not causing catalytic poisoning	unlimited, when used for gases not causing catalytic poisoning	unlimited, when used with gases that do not attack aluminium, rhenium-tungsten or gold	12 months to 5 years depending on the measuring cell	approx. 5 years	
Supply voltage	18 V – 30 V	18 V – 30 V	18 V – 30 V	18 V – 30 V	18 V – 30 V	18 V – 30 V
Interface	3-wire techniques 4–20 mA	3-wire techniques 4–20 mA	3-wire techniques 4–20 mA	3-wire techniques 4–20 mA	3-wire techniques 4–20 mA	3-wire techniques 4–20 mA
Type of protection	II 2 G	II 2 G	II 2 G	II 2 G	II 2 G	II 2 G
Ex-version	Ex de iamb IICT4Gb KEMA	Ex de iamb IICT4Gb KEMA	Ex de iamb IICT4Gb KEMA	Ex de iamb IICT4Gb KEMA	Ex de iamb IICT4Gb KEMA	Ex de iamb IICT4Gb KEMA
Protection class	IP 54	IP 54	IP 54	IP 54	IP 54	IP 54
Dimensions (W x H x D)	150 x 170 x 105 mm	150 x 170 x 105 mm	150 x 170 x 105 mm	150 x 170 x 105 mm 150 x 200 x 105 mm (O ₂)	150 x 170 x 105 mm	150 x 170 x 105 mm
Weight	2,7 kg	2,7 kg	2,7 kg	2,7 kg	2,7 kg	2,7 kg

Optional: fully-fledged Single-Channel-Gaswarning unit – not Ex

Voltage Supply	230 V, 50 Hz 115 V, 60 Hz (optional)	230 V, 50 Hz 115 V, 60 Hz (optional)	230 V, 50 Hz 115 V, 60 Hz (optional)
Power consumption	10 VA	10 VA	10 VA
Interface	4 potential-free changeover contact for alarm/failure 1 current output 4–20 mA 1 digital input for cancelling alarms	4 potential-free changeover contact for alarm/failure 1 current output 4–20 mA 1 digital input for cancelling alarms	4 potential-free changeover contact for alarm/failure 1 current output 4–20 mA 1 digital input for cancelling alarms

PEDAK meettechniek BV
P.O. Box 3030
NL - 6093 ZG Heythuysen
Tel.: +31(0)475 - 497424
Fax: +31(0)475 - 497425