



MULTI-CHANNEL GAS WARNING SYSTEM

GW 399

COMPACT



STANDARD





Application

The multi-channel gas warning system GW 399 continuously monitors the ambient air and provides an early warning of hazardous, explosive and non-combustible gases and vapours.

Fields of Application

- Monitoring of heating systems
- Garages and tunnels
- Liquid gas storage rooms
- Laboratories
- Cold-storage houses
- Plastic processing plants
- Chemical industries
- Paint manufacturing plants
- Concentration measurement of O₂
- and many more

Features

- Use of various types of measurement sensor
- Direct warning status recognition, via different colors of the LC-Display background illumination
- Menu-aided operation, via 2 keys
- Three alarm thresholds individually adjustable from 5–100 % of the test range
- Three floating alarm outputs for driving additional warning and control systems
- Floating relay contacts
- Serial output, RS 232 or RS 485
- LON[®]-Interface
- 4–20 mA current output
- Different housings are available e.g. 19" rack, panel mounting, wall-mounted housing
- Up to 10 units per rack
- 1 control unit configurable as master, for supervision of central alarms and communication control systems
- High degree of reliability
- Low current consumption
- Possibility of uninteruptible power supply

Measurable gases

Gas	Formula
Acetylene	C ₂ H ₂
Alcohol	e.g. C ₂ H ₆ O
Ammonia	NH ₃
Butane	C ₄ H ₁₀
Carbon dioxide	CO ₂
Carbon monoxide	CO

Carbon tetrachloride	CCl ₄
Chloroform	CHCl ₃
Ether	C ₄ H ₁₀ O
Helium	He
Hydrogen	H ₂
Hydrogen chloride	HCL
Methane (Natural gas)	CH ₄
Neon	Ne
Oxygen	O ₂
Petroleum spirit	
Propane	C ₃ H ₈
Toluene	C ₇ H ₈
Xylene	C ₈ H ₁₀

Accessories

Signal horn, Warning light, Warning banner, Ventilation control, Test meters, Plotter.

Additional accessories are available, depending on the system ordered.

Technical Data

Details as for control unit

Sensors:	Semiconductor sensor Heat reaction sensor Thermal conductivity sensor Chemical sensor Infrared sensor
Sensors input:	1 two-wire sensor (e.g. 592 TOX) or 1 three-wire sensor (e.g. GTR 196)
Sensor supply:	20 V = / 200 mA
Ranges:	Adaptable by software
Accuracy:	< 2 %, f.s.d.
Ambient temperature:	10 °C... + 40 °C
Temperature effects:	< 2 % for a ± 20 °C change
Installation:	Panel-mounting or Wall-mounting
Output signals:	Current output 4–20 mA RS 232 or RS 485 interface LON [®] -Interface 3 Alarm relays, 1 Fault relay
Relay rating:	115 V, 450 VA, other voltages on request
Voltage supply:	115 V, 60 Hz
Options:	230 V, 50 Hz, 24 V =, 12 V =
Power consumption:	8 VA