

123-2C DISPLAY

Two color display for the differential pressure, humidity and temperature.



Specifications:

- * LC-display 1x8 characters with 12mm character height.
- * 2-color red or green (programmable)
- * 0..20mA / 0..10V analogue input
- * 12..30VDC power supply

Dimensions:

- * 123-2C-1D: 122mm x 110mm
- * 123-2C-2D: 196mm x 110mm
- * 123-2C-3D: 270mm x 110mm

General information:

The new display for clean rooms, operating rooms or laboratories gives the users the status of the climate in their working space.

Due to the two color displays the users know directly if the climate is within the correct range. The color changes from green to red when the climate is out of specifications. Beside the color is also the measured value displayed.

Due to the modular design the user chooses 1, 2 or 3 displays in an aluminum panel, depending on which values he wants to be displayed.

The display has an analogue input which can be scaled. Also the characteristics, set points and hysteresis can be fully programmed over three keys.

Advantages

- * Flat design for build in wall
- * 2 Color for alarm or OK-status
- * Fully programmable
- * Modular design
- * Can be used together with almost any sensor without interfering the analogue output of the sensor.

Applications:

- * clean rooms
- * operating rooms
- * laboratories

PEDAK meettechniek BV

Roorveld 1

Tel: +31-475 497424

email: info@pedak.nl

6093 PL HEYTHUYSEN

Fax: +31 475 497425

www.pedak.nl