

# HOBO® Pendant™ G Logger

onset

- Records tilt, orientation, motion and activity
- Small, lightweight, waterproof logger can be deployed almost anywhere
- Maximum 100 Hz sampling rate provides detailed motion data
- Data readout in less than 30 seconds via fast Optic USB interface
- Long-lasting user-replaceable battery

## HOBO Pendant™ G Logger #UA-004-64



Size/Weight:  
5.8 x 3.3 x 2.3 cm  
(2.3 x 1.3 x 0.9 in)  
18 g (0.6 oz)

## Pendant Base Station #BASE-U-1



Memory: 64,000 1-axis measurement  
32,000 2-axes measurements  
21,333 3-axes measurements  
Sample rate: 100 per second (100 Hz) to 18 hours, user-selectable  
Battery life: 1-year (typical)—user-replaceable

**Acceleration**  
Measurement range:  $\pm 3G$   
Accuracy:  $\pm 2.5\%$  FS @ 25°C (77°F)—Factory calibrated  
Resolution (8-bit): 0.02G



- Offloads full Pendant logger in 30 seconds or less
- Splash resistant for reliable operation

### HOBO Pendant G Logger Ordering Information

Description	Part No.
HOBO Pendant G Logger (includes cable and magnet)	UA-004-64

### Software and Communication

*HOBOWare includes USB Interface cable*

HOBOWare® Pro Software (Windows®)	BHW-PC
HOBOWare Pro Software (Mac)	BHW-MAC
HOBOWare Lite (Windows/Mac)	BHW-LITE
Pendant Base Station*	BASE-U-1

### Optional Communications

HOBO U-Shuttle	U-DT-1
HOBO Waterproof Shuttle with Couplers	U-DTW-1

\*HOBO Waterproof Shuttle can also be used as a Base Station